

KENWOOD

Listen to the Future



TK-863G

Compact UHF FM Mobile Radio
Conventional & Trunked

GENERAL FEATURES

- 25W, 450-490 MHz
- 32 Systems / 250 GID
- 8 Character Alphanumeric Aliases
- Backlit LCD & Keys
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- 10 Programmable Function Keys
- Inverting Front Panel
- Internal Speaker
- Companded Audio
- Encryption / ANI Board Control
- Emergency Call Features
- DTMF Encode
- Time Out Timer
- Busy Channel Lockout
- Accessory Interface Cable Option
- Ignition Sense ¹
- Public Address / Horn Alert Option ²
- MIL-Spec Standard Mic Included
- MIL-Spec Noise-canceling Mic Option
- MIL-Spec 12-Key Noise-canceling Mic Option
- Windows Programming & Tuning
- Windows Firmware Uploading
- Front Panel Test / Tune
- Cloning
- MIL-STD-810 C/D/E/F

CONVENTIONAL SYSTEMS

- QT / DQT
- Single Priority Scan

TRUNKED SYSTEMS

- Kenwood LTR[®] Features



Options

<p>■ KMC-9C Control Station Desktop Microphone</p> 	<p>■ KCT-19 Accessories Connector Cable</p> 	<p>■ KES-5 External Speaker</p> 	<p>■ KLF-2 Line Noise Filter</p> 
<p>■ KMC-27A Microphone (MIL-SPEC Noise-Canceling)</p> 	<p>■ KCT-35 Extension Cable for KGP-2A/2B & KDS-100</p> 	<p>■ KMB-10 Key Lock Adapter</p> 	<p>■ KAP-1 PA/HA Unit</p> 
<p>■ KMC-27B Microphone</p> 	<p>■ KCT-36 Extension Cable</p> 	<p>■ KMB-20 Mounting Case</p> 	<p>■ KDS-100 Mobile Data Terminal</p> 
<p>■ KMC-28A Keypad Microphone (MIL-SPEC Noise-Canceling)</p> 	<p>■ KES-3 External Speaker</p> 	<p>■ KPS-15 DC Power Supply</p> 	<p>■ KGP-2A/2B GPS Receiver / Modem Unit</p> 

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-863G
GENERAL	
Frequency Range	450-490 MHz
Number of Systems	Max. 32
Number of Groups	Max. 250
Number of Channels (Conventional)	Max. 600
Channel Spacing	
Wide	25 kHz
Narrow	12.5 kHz
Channel Step	5 kHz, 6.25kHz
Channel Spread	40 MHz
Current Drain	
Standby	Less than 0.4 A
Receive	Less than 1.0 A
Transmit	Less than 8.0 A
Antenna Impedance	50 Ω
Operating Voltage	13.6 V DC ± 20 %
Operating Temperature Range	-22° F ~ +140° F (-30° C ~ +60° C)
Frequency Stability	±0.00025% (-22° F ~ +140° F)
Dimensions (W x H x D)	5-1/2 x 1-1/2 x 5-3/4 in. (140 x 40 x 145 mm)
Weight (net)	2.07 lbs. (940 g)
FCC ID	ALH29383110

Model	TK-863G
RECEIVER (Measurements made per EIA/TIA-603)	
Sensitivity (12dB SINAD)	
Wide	0.28 μV
Narrow	0.35 μV
Selectivity	
Wide	80 dB
Narrow	65 dB
Intermodulation Distortion	
Wide	75 dB
Narrow	63 dB
Spurious Response	85 dB
Audio Output	4 W with less than 5% distortion
TRANSMITTER (Measurements made per EIA/TIA-603)	
RF Power Output	25 W
Spurious	65 dB
FM Noise	
Wide	50 dB
Narrow	45 dB
Modulation	
Wide	16KØF3E
Narrow	11KØF3E
Audio Distortion	Less than 3%

Kenwood follows a policy of continuous advancement in development.
For this reason specifications may be changed without notice.

LTR® is a registered trademark of Transcript International.

Applicable MIL-STD

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Sand & Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I Cat.8	514.4/Procedure I Cat.8	514.5/Procedure I Cat.20
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V

footnotes from front:

¹ Ignition sense requires KCT-18, 19.

² Public Address / Horn Alert Option requires KAP-1 PA/HA Unit and KCT-19 ACC Cable Options.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification